

## DATA SHEET TECNOCLEAN 150

transparency for windows COD. 3360/150

Data sheet

Water repellent product that makes the windows more transparent and clear and cancels the imprints of the working suction cups forever.

This variant, while maintaining the characteristics of the TECNOCLEAN basic product, provides greater transparency to the glass, with less reflective effect - giving greater clarity to objects protected by glass. With the TECNOCLEAN treatment the glass is protected against corrosion, blurring and scratches, keeping the glass transparent as new, not allowing the glass to oxidize by means of atmospheric factors.

Many glassworks use the TECNOCLEAN 150 treatment both in the company and during the assembly phase, also to cancel the annoying and unsightly impressions of the working suction cups.

It is applied directly on new substrates, without the need for special preparation and cleaning treatments. For substrates used before the application of the TECNOCLEAN treatment, deep cleaning with REMOV GEL is required (SUPERGLASS in the case of a very dirty and encrusted surface) to remove limestone and very resistant dirt.

Thanks to a chemical reaction, with a single application, the coating becomes one with the glass surface and makes it non-stick, water-repellent, dirt-repellent, antibacterial and well protected against corrosion, aging, obfuscation and scratches.

The advantages of the TECNOCLEAN 150 transparency treatment

aesthetics: less reflected effect then more clarity and more transparency. I always look clean and brighter, longer intervals between cleaning. It resists to superficial contaminations like smog, limestone and sodium deposits etc., scratches and wear (also from atmospheric dust such as winds mixed with sand, saltiness), stains and obfuscation and signs of aging and corrosion of the glass maintaining the appearance and the performances original glass.

functional: provides greater transparency to the glass, thus giving greater clarity to objects protected by glass. It eliminates forever the problems with the imprints of the working suction cups.

On the treated glass, dust and dirt adheres much less.

Very easy to clean surfaces avoiding aggressive and abrasive cleaning methods.

After some time, limescale roughness or marks caused by abrasives used in more aggressive cleaning will begin to form on the untreated surface.

hygienic: neutralization of water deposits; the water flows away very quickly and without leaving residues it drags with it dirt, limestone, salts, bacteria. In the case of windows exposed to the elements, it facilitates the removal of the deposited dirt with the subsequent rains.

Long life, UV stability, easy application even on already installed supports

The treatment is NOT toxic and can be repeated without contraindications to the first signs of abrasion; overlapping treatments do not increase its efficiency or duration.

It is important to remember that some behaviors can compromise the duration:

- autoclaving;

- the use of caustic detergents or abrasive sponges;
  - prolonged stay in contact with alkaline solutions.
- Do not affect the efficiency of the treatment instead:
- washing also repeated in the dishwasher at 70 °
  - detergents, disinfectants, dyes, acids.

#### TECNOCLEAN Performance:

spray 40-45 square meters / liter  
with buffer 65 - 75 sqm / liter  
125 ml bottle, buffer 7-9 sqm

#### WARNINGS

THE PRODUCT MUST BE KEPT OUT OF THE REACH OF CHILDREN  
AND MUST BE USED EXCLUSIVELY WITH GLOVES, GLASSES AND IN ARRANGED LOCAL, AVOIDING DIRECT  
INHALATION.

ATTENTION TO THE PRODUCT SAFETY DATA SHEET.

FOR MIRRORS: DO NOT ABSOLUTELY PASS THE PRODUCT IN THE BACK OF THE GLASS, DAMAGE THE  
MIRROR.

DO NOT USE ON CHROMATURES, ALUMINUMS AND PLASTICS AS WELL AFTER THE APPEARANCE.

IN DOMESTIC ENVIRONMENTS KEEP THE AREA WELL-AREA TO AVOID ACCUMULATION OF HARMFUL  
VAPORS FOR HEALTH AND CHROMED ACCESSORIES.

#### INSTRUCTIONS FOR USE

Shake the product before use. The product must NOT be stretched with other substances or water.  
Do the job in a well-ventilated area.

TECNOCLEAN treatment on new surfaces:

1. TECNOCLEAN apply the product abundantly and evenly on the perfectly clean and dry surface using a  
cotton wool pad (= cotton wool), soaked with the TECNOCLEAN product

If the metal or plastic of the frame profiles is wet, wipe off with a dry cloth immediately while working  
It is very important to use a cotton pad and put an abundant quantity of product on the glass or ceramic  
and spread it evenly to see the product wet glass and ceramics.

If the product is too little, the right reaction does not take place:  
only an abundant amount applied, it succeeds